

02 - 23 - 00

17

**UTILITY PATENT APPLICATION TRANSMITTAL**  
**(Large Entity)***(Only for new nonprovisional applications under 37 CFR 1.53(b))*Docket No.  
PO9-99-151Total Pages in this Submission  
40 pages**TO THE ASSISTANT COMMISSIONER FOR PATENTS**Box Patent Application  
Washington, D.C. 20231

Transmitted herewith for filing under 35 U.S.C. 111(a) and 37 C.F.R. 1.53(b) is a new utility patent application for an invention entitled:

**Identity Vectoring Via Chained Mapping Records**

and invented by:

**Richard H. Guski; Walter B. Farrell; James W. Sweeny; Thomas J. Szczygielski and John M. Thompson**If a **CONTINUATION APPLICATION**, check appropriate box and supply the requisite information:☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: \_\_\_\_\_

Which is a:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: \_\_\_\_\_

Which is a:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: \_\_\_\_\_

Enclosed are:

**Application Elements**

1. ☒ Filing fee as calculated and transmitted as described below
2. ☒ Specification having 24 pages and including the following:
  - a. ☒ Descriptive Title of the Invention
  - b. ☐ Cross References to Related Applications *(if applicable)*
  - c. ☐ Statement Regarding Federally-sponsored Research/Development *(if applicable)*
  - d. ☐ Reference to Microfiche Appendix *(if applicable)*
  - e. ☒ Background of the Invention
  - f. ☒ Brief Summary of the Invention
  - g. ☒ Brief Description of the Drawings *(if drawings filed)*
  - h. ☒ Detailed Description
  - i. ☒ Claim(s) as Classified Below
  - j. ☒ Abstract of the Disclosure

**UTILITY PATENT APPLICATION TRANSMITTAL**  
**(Large Entity)**

*(Only for new nonprovisional applications under 37 CFR 1.53(b))*

Docket No.  
**PO9-99-151**

Total Pages in this Submission  
**40 pages**

**Application Elements (Continued)**

3. ☒ Drawing(s) *(when necessary as prescribed by 35 USC 113)*
- a. ☐ Formal                      Number of Sheets \_\_\_\_\_
- b. ☒ Informal                      Number of Sheets 4
4. ☒ Oath or Declaration
- a. ☐ Newly executed *(original or copy)*                      ☒ Unexecuted
- b. ☐ Copy from a prior application (37 CFR 1.63(d)) *(for continuation/divisional application only)*
- c. ☒ With Power of Attorney                      ☐ Without Power of Attorney
- d. ☐ DELETION OF INVENTOR(S)  
Signed statement attached deleting inventor(s) named in the prior application,  
see 37 C.F.R. 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation By Reference *(usable if Box 4b is checked)*  
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied  
under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby  
incorporated by reference therein.
6. ☐ Computer Program in Microfiche *(Appendix)*
7. ☐ Nucleotide and/or Amino Acid Sequence Submission *(if applicable, all must be included)*
- a. ☐ Paper Copy
- b. ☐ Computer Readable Copy *(identical to computer copy)*
- c. ☐ Statement Verifying Identical Paper and Computer Readable Copy

**Accompanying Application Parts**

8. ☐ Assignment Papers *(cover sheet & document(s))*
9. ☐ 37 CFR 3.73(B) Statement *(when there is an assignee)*
10. ☐ English Translation Document *(if applicable)*
11. ☒ Information Disclosure Statement/PTO-1449                      ☒ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Acknowledgment postcard
14. ☒ Certificate of Mailing
- ☐ First Class                      ☒ Express Mail *(Specify Label No.):* EK350348613US

**UTILITY PATENT APPLICATION TRANSMITTAL**  
**(Large Entity)**

*(Only for new nonprovisional applications under 37 CFR 1.53(b))*

Docket No.  
PO9-99-151

Total Pages in this Submission  
40 pages

**Accompanying Application Parts (Continued)**

15. ☐ Certified Copy of Priority Document(s) *(if foreign priority is claimed)*

16. ☐ Additional Enclosures *(please identify below):*

**Fee Calculation and Transmittal**

**CLAIMS AS FILED**

For	#Filed	#Allowed	#Extra	Rate	Fee
Total Claims	24	- 20 =	4	x \$18.00	\$72.00
Indep. Claims	3	- 3 =	0	x \$78.00	\$0.00
Multiple Dependent Claims (check if applicable) <input type="checkbox"/>					\$0.00
BASIC FEE					\$690.00
OTHER FEE <i>(specify purpose)</i>					\$0.00
TOTAL FILING FEE					\$762.00

- ☐ A check in the amount of \_\_\_\_\_ to cover the filing fee is enclosed.
- ☒ The Commissioner is hereby authorized to charge and credit Deposit Account No. 09-0463 as described below. A duplicate copy of this sheet is enclosed.
- ☒ Charge the amount of \$762.00 as filing fee.
  - ☒ Credit any overpayment.
  - ☒ Charge any additional filing fees required under 37 C.F.R. 1.16 and 1.17.
  - ☐ Charge the issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance, pursuant to 37 C.F.R. 1.311(b).

Signature

William A. Kinnaman Jr. - Attorney  
Registration No.: 27,650  
IBM Corporation  
Intellectual Property Law  
2455 South Road, M/S P386  
Poughkeepsie, New York 12601  
Telephone: (914) 433-1175  
Facsimile: (914) 432-9601

Dated: February 22, 2000

CC:

Docket No : PO9-99-151

Inventor : Guski, et al.

Title : IDENTITY VECTORING VIA  
CHAINED MAPPING RECORDS

APPLICATION FOR UNITED STATES  
LETTERS PATENT

"Express Mail" Mailing Label No.: EK350348613US  
Date of Deposit: February 22, 2000

I hereby certify that this paper is being deposited with the United States Postal Service as "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to: Box Patent Application, Assistant Commissioner for Patents, Washington, D.C. 20231.

Name: Billy R. Stacy

Signature: Billy R. Stacy

INTERNATIONAL BUSINESS MACHINES CORPORATION

## IDENTITY VECTORING VIA CHAINED MAPPING RECORDS

### FIELD OF THE INVENTION

The present invention generally relates to user authentication and authorization on a computer network, more specifically, to network authentication and authorization using  
5 identity vectoring via chained mapping records.

### BACKGROUND OF THE INVENTION

Network operating systems often include access control systems (security systems) for controlling access to entities that are stored on the network or coupled to the network. The term "entity" includes hardware such as gateways to other networks, printers, and  
10 modems, as well as software such as directories, files, application programs, data, records, fields in a record, and cells in a spreadsheet--in other words, virtually any hardware or software resource of a computer network. Regardless of whether the network is simply two computers coupled peer-to-peer, or a wide area network with thousands of users, the access control system for the network will typically require authentication and authorization of the  
15 network's users. That is, the system will identify each user that can connect to the network (authentication) and limit the user's access rights to those entities on the network (authorization).

In large networks, a user may need to access a number of different access control systems, either explicitly, through manually logging onto the systems, or implicitly, where  
20 an application running on a client workstation interacts with a number of server applications. For example, a user may need to access the functions of an office network from the Internet using a Secured Sockets Layer (SSL) protocol. In such networks, public key cryptographic systems have been widely used to authenticate the user.

Public key cryptographic systems are well known. In public key cryptographic systems, a trusted authority may create a digital message, which contains a user's public key and the name of the user. A representative of the trusted authority (Certificate Authority) digitally signs the digital message with the authority's own signature to verify that the public key does indeed belong to the named user. A standard way of encoding such digital messages, known as digital certificates, is described in the X.509 V3 standard. In an X.509 digital certificate, the user's "name" is the user's distinguished name within the X.500 architecture. The X.500 architecture describes a tree-like naming scheme, wherein each entity on the network has a unique, or distinguished, name.

Access control systems for some Internet-based networks employ the user's X.500 distinguished name from the X.509 digital certificate to both authenticate and authorize the user. In such systems, the X.500 distinguished name is mapped (correlated) to user's credentials using a mapping record within a security registry. The mapping record contains a user namespace identification (user ID) or similar logon information corresponding to a single distinguished name. A number of these mapping records are stored in a security registry, which contains at least one mapping record for each digital certificate that the access control system is to recognize. If the X.500 distinguished name is recognized (i.e. contained in one of the mapping records), the ID corresponding to that distinguished name will be used to establish a network access environment wherein the user is provided access authorized entities on the network. One example of such an access control system is described in U.S. Patent 5,922,074, issued on July 13, 1999, and entitled "Method and Apparatus for Providing Secure Distributed Directory Services and Public Key Infrastructure."

The use of mapping records eliminates the need for the user to authenticate with more than one server on the same network. In addition, the user ID provided by the mapping record can be used to authorize the user's access rights to entities on the network. However,

the use of mapping records and directory databases have several drawbacks. For example, the number of users that can be supported is limited by the number of mapping records that the database can handle. This drawback is exacerbated by the fact that the mapping record points to one, and only one, user ID.

## 5 SUMMARY OF THE INVENTION

A method of identity vectoring using chained mapping records includes comparing a distinguished name or partial distinguished name with a plurality of mapping records. A mapping record matching the distinguished name or partial distinguished name is located. A variable from the matching mapping record is then replaced by an environmental factor  
10 to create a new search criteria. The new search criteria is then compared with the plurality of mapping records.

With this invention, the environmental factors have the effect of automatically directing, or "vectoring," the mapping process to its final selection and conclusion. This invention adds flexibility to the current implementation of identity mapping by allowing a  
15 mapping record to "point to" multiple user IDs with the final selection of the mapping record (to which the digital certificate will be mapped) based on network environmental factors.

## BRIEF DESCRIPTION OF THE DRAWINGS

Referring now to the drawings wherein like elements are numbered alike in the several FIGURES:

20 FIG. 1. is a block diagram of the resources, entities, and users coupled on a exemplified computer communications network;

FIG. 2. is a data flow diagram of a client/server relationship including an access control system of the present invention;

FIG. 3. is a data flow diagram of the access control system of FIG. 2;

FIG. 4 is a flow chart of the identity vectoring method used in the access control system of FIG. 2; and

FIG. 5. is a graphical representation of an X.500 directory information tree.

## 5 DETAILED DESCRIPTION OF THE INVENTION

Referring to FIG. 1, an exemplified block diagram network is shown generally as 10. The network 10 employs multiple client/server entities interconnected via local or wide area networks (LAN or WAN) 12, 30 and the Internet 18. The networks 12, 18, 30 shown are intended to be representative of the many network designs such as Ethernet, token ring, etc.  
10 These networks employ a variety of protocols such as NETBIOS and TCP/IP.

Network 12 includes PC-type computers 16 to provide a plurality of client processes (clients). Such client processes would include any process that makes requests for network resources (entities). A client may also be hardware or circuitry embodied in, for example, a Smart Card Reader requesting information or services. Computers, such as PC-type  
15 computers 16, that provide one or more client processes are hereinafter referred to as client computers. Client computers 16 allow users to connect to network resources such as printers 24 and 26.

A computer system 14 (e.g., a mainframe or minicomputer) provides one or more server processes (servers) to the network, and may also run one or more client processes.  
20 Minicomputer 14 may, for example, run IBM Corporation's commercially available OS/390 operating system, and servers operating on minicomputer 14 may include a web server, such as IBM's commercially available Domino Go Web Server™( (WebSphere Application Server™), a security server, such as IBM's commercially available O/S390 Security



Server™, an E-mail server, a print server or any other process that fulfils requests for information services. Forming part of at least one of these servers, or itself being a server, is an access control system, which provides authentication and authorization functions for clients and servers within an X.500 namespace. One example of such an access control system is Resource Access Control Facility (RACF)™, which forms part of the O/S390 Security Server™. Computers, such as minicomputer 14, that provide one or more server processes are hereinafter referred to as server computers.

Other networks, such as network 30, communicate with network 12 via the Internet 18 through routers 20 and 22. Network 30 includes workstations 32, which may, for example, be an IBM PC, operating as both a client and a server computer. Remote client computers 28 may communicate with the Internet 18 via phone lines 34 and router 20 to network 12.

Although network 30 is shown connected to network 12 via the Internet 18, any other network connection might be utilized without interference with the present invention. Thus, for example, an intra-office network that distributes digital certificates may be used with the present invention. Finally, the network block diagram 10 is shown by way of illustration and not limitation.

FIG. 2 is a data flow diagram showing a client/server relationship including the access control system 50 of the present invention. The client (user) 52 may be, for example, any client process operating on any of the client computers described above in conjunction with FIG. 1. Similarly, the access control system 50 may operate on any of the server computers described above in conjunction with FIG. 1. Located between the client 52 and the access control system 50 is a resource manager 54. Resource manager 54 is, for example, a server, an application, or a print or data manager on the network. Resource manager 54 may include, for example, IBM's commercially available Domino Go Web Server™(

(WebSphere Application Server™), TSO/E™ time-share server, Lotus Notes for O/S390™, Novell Directory Services for O/S390™, or O/S 390 Distributed Computing Environment (DCE)™ or UNIX features. A security registry 56 stores a plurality of mapping records, which include information regarding individual users and corporate entities. For example, such a security registry is implemented in IBM O/S390 Security Server RACF™ component.

FIG. 3 is data flow a diagram of the access control system 50. The access control system 50 includes a certificate mapping and authenticated security context mapping process 100 which receives as input one digital certificate 102 from the resource manager 54 (FIG. 2). Process 100 interacts with one or more of a plurality of mapping records 106 from security registry 56 (FIG. 2). The plurality of mapping records 106 include distinguished name mapping records 108 and criteria mapping records 110. Each distinguished name mapping record 108 corresponds to a distinguished name recognized by the network, and includes a data field including a user ID or variable name, as will be described in further detail hereinafter. The distinguished name mapping record 108 represents a complete distinguished name or some portion of a distinguished name (e.g. X.500 distinguished name). Each criteria mapping record 110 corresponds to an environmental factor used in the chained mapping process, which is described in further detail hereinafter, and a data field including a user ID or variable name. An authenticated security context control block 104 (e.g., IBM's RACF Accessor Control Environmental Element (ACEE)) is generated by process 100 after the user ID corresponding to the digital certificate 102 is determined by process 100. The authenticated security context control block 104 includes the necessary user credentials for establishing an network access environment for the user.

Referring to FIG. 2 and FIG. 3, the operation of the access control system 50 can be shown. Client 52 initiates communication with the resource manager 54. The resource manager 54 responds to the connection and demands that the client 52 identify itself. Client

52 is identified and authenticated over the SSL secured communications protocol using digital certificate 102 (e.g. an X.509 Version 3 digital certificate). The resource manager 54 then provides digital certificate 102 to the access control system 50. Within access control system 50, the certificate mapping and authenticated security context mapping process 100  
5 employs an identity vectoring (selection) method, described hereinafter, to find mapping record(s) 106 within directory database 56 that corresponds to the distinguished name from the digital certificate 102. After the appropriate mapping record(s) 106 is/are found, process 100 creates an authenticated security context control block 104 using the user ID from the mapping record(s) 106. The authenticated security context control block 104 is then passed  
10 from the access control system 50 to the resource manager 54. The authenticated security context is then assigned to the individual user's processing thread within the resource manager's process. The resource manager 54 can then use the authenticated security context to authorize the client/user's 52 access to resources on the network.

Operation of the certificate mapping and authenticated security context mapping  
15 process 100 will now be shown by reference to FIG. 3 and FIG. 4, where FIG. 4 is a flow chart of the identity vectoring method 150 used within the certificate mapping and authenticated security context mapping process 100 of FIG. 3. Method 150 begins at block 152 where a digital certificate 102 is received by the authenticated security context mapping process 100. Method 150 then proceeds to block 154 where the distinguished name from the  
20 digital certificate 102 is compared with distinguished name mapping records 108. If no match is found, method 150 continues to block 156 where a portion (node) of the distinguished name is deleted to create a partial distinguished name (partial path name). If there are any more nodes (i.e., the last node has not been eliminated in block 156) then method 150 continues from block 158 to block 154, where the partial distinguished name is  
25 compared with distinguished name mapping records 108. If there are no more nodes (i.e., the last node was eliminated in block 156) then access is denied at block 160 and method 150

ends.

If, in block 154, the distinguished name or partial distinguished name matches one of the distinguished name mapping records 108, method 150 continues at block 162. At block 162, it is determined whether or not the data field for the matching distinguished name mapping record 108 contains a user ID or a variable name. If the data field contains a user ID, an authenticated security context control block 104 is created using the user ID from that distinguished name mapping record 108, and the authenticated security context control block 104 is returned to the resource manager at block 164. Method 150 then ends. However, if the data field does not contain a user ID (i.e., it contains a variable name), then method 150 continues at block 166.

At block 166 the variable name is replaced with an environmental factor associated with the variable name existing at the time the digital certificate was received by process 100 in block 152. Replacing the variable name with the environmental factor creates a new search criteria. Method 150 then continues at block 168 where the search criteria is compared to the criteria mapping records 110. If no criteria mapping record 110 matches the criteria name, access is denied in block 160 and method 150 ends. If a matching criteria mapping record 110 is found, then the data field of the matching criteria mapping record 110 is checked for a user ID (as before) in block 162. Method 150 continues as described until either a user ID is found in block 162 or no more criteria matches occur in block 168.

At any point in the identity vectoring method 150 when a sought mapping record 106 is not found and the user's distinguished name cannot be reduced further, the request processing ends, usually resulting in the failure of the original request, e.g. at sign-on.

It is evident that mapping record 106 data fields could be defined so as to put method 150 into a loop. However, an actual implementation would keep track of all chain traverses

and end the process if such a loop occurs.

Examples of the operation of identity vectoring method 150 can now be shown by reference to FIG. 3, FIG. 4, and FIG. 5, where FIG. 5 is an X.500 directory information tree. As noted previously, the user's distinguished name from the digital certificate 102 identifies the user's location in the X.500 directory information tree. In block 156 of method 150, an attempt is made to determine the user's ID by comparing the user's distinguished name with distinguished name mapping records 108. For the tree shown in FIG. 3, John Doe's X.500 distinguished name is:

/O=IBM/OU=S390/OU=POK/OU=BWVA/CN=John Doe (1)

Or, written in the address form recognized by IBM's O/S390 Security Server RACF™ component, the distinguished name mapping record 108 matching John Doe's distinguished name would be:

CN=John Doe, OU=BWVA, OU=POK, OU=S390, O=IBM (2)

Where each level of the X.500 tree (i.e. each portion of the distinguished name) represents one node. The interpretation of the nodes in the tree structure of FIG.1 is that John Doe works in department BWVA in Poughkeepsie for the S390 division of the IBM corporation. A user ID may be assigned for each node level in the X.500 tree, with the ID providing authorization for resources at that node level. Using the above example, assume that node OU=Poughkeepsie is assigned a user ID POKUSR, and node OU = BWVA is assigned user ID BWVAUSR. John's name matches both nodes, so the more specific node, OU=BWVAUSR is used, associating John with user ID BWVAUSR and the access rights to resources associated with that user ID and node level.

At block 154 of method 150, the distinguished name and distinguished name

mapping record, shown at (1) and (2) above, would be compared. Distinguished name (1) and distinguished name mapping record (2) are exact matches (i.e. their nodes match one-to-one). Therefore, method 150 would continue from block 154 to block 162. In addition, because distinguished name mapping record (2) is associated with a user ID (BWVAUSR),  
5 method 150 would continue to block 164 where an authenticated security context control block 104 is created using the user ID. However, if distinguished name mapping record (2) were associated with a variable and not a user ID, method 150 would continue to block 166.

Returning to block 154, if no matching distinguished name mapping record 108 exists for the distinguished name, method 150 continues to block 156 where one node from the  
10 distinguished name would be deleted to create a partial distinguished name. For distinguished name (1), the first partial distinguished name is OU=BWVA, OU=POK, OU=S390, O=IBM, the next partial distinguished name is OU= POK, OU=S390, O=IBM, etc.. After the node is deleted, the partial distinguished name is checked for a matching distinguished name mapping record 108 at block 154. Method 150 continues in this manner  
15 until all of the nodes have been eliminated or a matching distinguished name mapping record 108 is found. If a matching distinguished name mapping record 108 is found, method 150 continues to block 162.

If, in block 162, the data field for the matching distinguished name mapping record 108 includes a variable name, which may be denoted by a special character added to the data  
20 field (e.g., "&"), then method 150 continues at block 166 where the search criteria to be used in the next mapping record search is derived by substituting an environmental factor existing at sign-on time for the variable name string in the data field. The variable name may correspond to one or more environmental factors. Environmental factors, as used herein, include any system and/or application statuses that may be in effect at the time the sign-on  
25 occurs. With this invention, these environmental factors have the effect of "vectoring" the

mapping records and therefore the user ID selection process to its final selection and conclusion.

The following are two examples of how such identity vectoring could be used. In these examples, the environmental factors are, in the first example, the target application requested by client/user 52, and, in the second example, the strength of encryption used for the SSL connection between client/user 52 and resource manager 54 (i.e., between client and server). It will be recognized, however, that the identity vectoring method described herein is not limited to these two environmental factors, but could include other environmental factors as well.

In the first example, mapping records 106 have been defined that will direct the certificate mapping process 100 to map one digital certificate 102 to two user IDs. The mapping records 106 include additional information that says, in effect, "map to the first user ID when the application the user is signing onto is the first application, else map to the second user ID". In this example, BobsBank, Inc. has two web based applications, an online banking application, and an online insurance application. It has contracted a certificate authority (e.g. VeriSign) to issue certificates to its user base. Each user will be issued only one certificate. When one of the company's users connects to the banking application using the certificate authority issued certificate, the user ID assigned should be BANKU. If the user connects to the insurance application using that same certificate, the user ID assigned should INSUREU. Thus, with reference to the X.500 tree of FIG. 5, the distinguished name mapping record108 would be:

mapping record:

OU=Bob'sBank,Inc. General Subscriber.O=Certificate Authority L=Internet

data field:

/APPLID=&APPLID

The "/" indicates to the certificate mapping process 100 that this is a variable name rather than a user ID. When digital certificate 102 is presented to certificate mapping process 100, and this variable name is found (blocks 154 and 162), certificate mapping process 100 substitutes the appropriate environmental parameter for &APPLID (block 166). In this case, the environmental parameter is the application ID, which is provided to certificate mapping process 100 by the resource manager 54. If the application being accessed is WEBBANK, then the substitution results in APPLID=WEBBANK. Next, mapping process 100 looks for a criteria mapping record 110 that matches the name APPLID=WEBBANK (block 168). This search would yield the user ID BANKU. Alternatively, if the application being accessed is WEBINS, then the substitution (block 166) results in APPLID=WEBINS, and process 100 looks for a criteria mapping record 110 to match the name APPLID=WEBINS (block 168). This search would yield the user ID INSUREU. In addition, if the certificate 102 could also be used for other applications besides the banking and insurance applications, and should be associated with a user ID, a generic criteria mapping record 110 would correspond to a search criteria APPLID=\*, where "\*" is a generic (wild card) value, could be created to cover all other applications.

In the second example, the environmental factor is the strength of encryption used for the SSL connection of client to server. The SSL protocol supports negotiating the encryption strength, allowing a connection to be either high strength, using at least 128 bits, or low strength, using 40 bits for encryption. In this example, BobsMart has contracted with a certificate authority to provide certificates to its account representatives, who access the company's system through SSL. Account representatives connect either through system A (SystemA in FIG. 5) or through system B (SystemB in FIG. 5), depending on the strength of the encryption. System A includes general information, and can be accessed using a low



strength encryption level, while system B includes sensitive information about the company's customers and should only be accessed using a high strength encryption level. Advantageously, the identity vectoring method 150 allows system A and system B to share the same distinguished name mapping record 108. Account representatives have resource  
5 access based on the user ID ACCTREP when using high strength encryption, and the user ID GENERAL when using low strength encryption. The resource manager 54 used to access system data has a variable that specifies the encryption level as either HIGH or LOW, based on the encryption strength negotiated by the SSL connection. This variable is passed when the resource manager 54 calls process 100 to identify and authenticate the user. The  
10 distinguished name mapping record 108 for the digital certificates of account representatives is:

mapping record: OU=BobsMart,Inc.General Subscriber, O=CertificateAuthority,  
Inc.L=Internet

data field: /ENCRLVL=&ENCRLVL

15 When a certificate is presented to process 100, the distinguished name mapping record 108 is found based on the user's distinguished name from the digital certificate 102 (block 154) , and /ENCRLVL=&ENCRLVL is found in the data field. The "/" that begins this field indicates to process 100 that this is a variable name rather than the user ID (block 162). The encryption level, ENCRLVL, cannot be a predefined value, as it may change  
20 independently of the type of user. This value must be passed to process 100 by the resource manager 54. For this example, the resource manager 54 has passed ENCRLVL with a value of LOW. Then, process 100 looks for a criteria mapping record 110 to match the name ENCRLVL=LOW (block 168), which yields the user ID GENERAL. The user ID GENERAL is then used to create an authenticated security context control block 104, which  
25 is returned to the resource manager 54 (block 164).



While a preferred embodiment has been shown and described, various modifications and substitutions may be made thereto without departing from the spirit and scope of the invention. Accordingly, it is to be understood that the present invention has been described by way of illustration and not limitation.

## CLAIMS

1           Claim 1.       A method of identity vectoring using chained mapping records, the  
2 method including:

3           comparing a distinguished name or a partial distinguished name with a plurality of  
4 mapping records;

5           replacing a variable from a first matching mapping record with an environmental  
6 factor to create a first search criteria, the first matching mapping record indicating the  
7 distinguished name or the partial distinguished name; and

8           comparing the first search criteria with the plurality of mapping records.

1           Claim 2.       The method of claim 1, further including:

2           generating a security context control block using a user identification from a second  
3 matching mapping record, the second matching mapping record indicating the first search  
4 criteria.

1           Claim 3.       The method of claim 1, further including:

2           replacing a variable from a second matching mapping record with an environmental  
3 factor to create a second search criteria, the second matching mapping record indicating the  
4 first search criteria.

1           Claim 4.       The method of claim 3, further including:

2           generating a security context control block using a user identification from a third  
3   matching mapping record, the third matching mapping record indicating the second search  
4   criteria.

1           Claim 5.       The method of claim 1, further including:

2           eliminating a portion of an X.500 distinguished name to create the partial  
3   distinguished name used in said comparing the partial distinguished name with the plurality  
4   of mapping records.

1           Claim 6.       The method of claim 1, further including:

2           generating a security context control block using a user identification from the first  
3   matching mapping record if the first matching mapping record includes the user  
4   identification.

1           Claim 7.       The method of claim 1, further including:

2           providing an X.500 distinguished name for use as the distinguished name used in said  
3   comparing the distinguished name with the plurality of mapping records.

1           Claim 8.       The method of claim 1, further including:

2           providing a system status for use as the environmental factor for said replacing the  
3   variable.

1           Claim 9.       A system for identity mapping using chained mapping records, the  
2   system including:

3           a digital certificate including a distinguished name;

4           a distinguished name mapping record indicative of at least a portion of said  
5   distinguished name, said distinguished name mapping record including a first data field, said  
6   first data field including a first variable indicative of a first environmental factor;

7           a first criteria mapping record corresponding to a first state of said first environmental  
8   factor, said first criteria mapping record including a second data field, said second data field  
9   including a first user identity; and

10          a mapping process configured to receive said digital certificate, wherein said mapping  
11   process generates a security context control block using said first user identity in response  
12   to said first state of said first environmental factor.

1           Claim 10.       The system of claim 9, further including:

2           a second criteria mapping record corresponding to a second state of said first  
3   environmental factor, said second criteria mapping record including a third data field, said  
4   third data field including a second user identity; and

5   wherein said mapping process is further configured to generate a security context control  
6   block using said second user identity in response to said second state of said first  
7   environmental factor.

1           Claim 11.       The system of claim 9, further including:

2           a second criteria mapping record corresponding to a second state of said first  
3   environmental factor, said second criteria mapping record including a third data field, said  
4   third data field including a second variable indicative of a second environmental factor;

5           a third criteria mapping record corresponding to said second environmental factor,  
6   said third criteria mapping record including a fourth data field, said fourth data field  
7   including a second user identity; and

8           wherein said mapping process is further configured to generate a security context  
9   control block using said second user identity in response to said second state of said first  
10   environmental factor and said third environmental factor.

1           Claim 12.     The system of claim 9, wherein said distinguished name is an X.500  
2 distinguished name.

1           Claim 13.     The system of claim 10, wherein said first user identity represents a  
2 first level of network authorization, and said second user identity represents a second level  
3 of network authorization.

1           Claim 14.     The system of claim 9, wherein said first environmental factor is a  
2 network status at the time said digital certificate is received by said mapping process.

1           Claim 15.     The system of claim 9, wherein said first environmental factor is an  
2 application status at the time said digital certificate is received by said mapping process.

1           Claim 16.     The system of claim 9, wherein said first environmental factor is  
2 included in said digital certificate.



1           Claim 17.     A storage medium encoded with machine-readable computer program  
2     code for mapping name space identities to digital certificates, the storage medium including  
3     instructions for causing a computer to implement a method comprising:

4           comparing a distinguished name or a partial distinguished name with a plurality of  
5     mapping records;

6           replacing a variable from a first matching mapping record with an environmental  
7     factor to create a first search criteria, the first matching mapping record indicating the  
8     distinguished name or the partial distinguished name; and

9           comparing the first search criteria with the plurality of mapping records.

1           Claim 18.     The storage medium of claim 17 further comprising instructions for  
2     causing a computer to implement:

3           generating a security context control block using a user identification from a second  
4     matching mapping record, the second matching mapping record indicating the first search  
5     criteria.

1           Claim 19.     The storage medium of claim 17 further comprising instructions for  
2     causing a computer to implement:

3           replacing a variable from a second matching mapping record with an environmental  
4     factor to create a second search criteria, the second matching mapping record indicating the  
5     first search criteria.

1           Claim 20.     The storage medium of claim 19 further comprising instructions for  
2 causing a computer to implement:

3           generating a security context control block using a user identification from a third  
4 matching mapping record, the third matching mapping record indicating the second search  
5 criteria.

1           Claim 21.     The storage medium of claim 17 further comprising instructions for  
2 causing a computer to implement:

3           eliminating a portion of an X.500 distinguished name to create the partial  
4 distinguished name used in said comparing the partial distinguished name with the plurality  
5 of mapping records.

1           Claim 22.     The storage medium of claim 17 further comprising instructions for  
2 causing a computer to implement:

3           generating a security context control block using a user identification from the first  
4 matching mapping record if the first matching mapping record includes the user  
5 identification.

1           Claim 23.     The storage medium of claim 17 further comprising instructions for  
2 causing a computer to implement:

3           providing an X.500 distinguished name for use as the distinguished name used in said  
4 comparing the distinguished name with the plurality of mapping records.


1           Claim 24.     The storage medium of claim 17 further comprising instructions for  
2 causing a computer to implement:

3           providing a system status for use as the environmental factor for said replacing the  
4 variable.

## IDENTITY VECTORING VIA CHAINED MAPPING RECORDS

### ABSTRACT

An identity vectoring method is accomplished by matching a distinguished name or partial distinguished name from a digital certificate with a distinguished name mapping record. A data field in the distinguished name mapping record includes either a  
5 mapping record. A data field in the distinguished name mapping record includes either a variable name or a user ID. The variable name corresponds to any environmental factor. The next mapping record to be considered, the criteria mapping record, is determined by substituting the environmental factor for the variable name in the data field. A data field in the criteria mapping record includes either a variable name or a user ID. The process  
10 completes when a mapping record containing only a user ID is encountered or when no matching criteria mapping records are found.






Fig. 2




Fig. 3




Fig. 4



Fig. 5

	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2423	2424	2425	2426	2427	2428	2429	2430	2431	2432	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---



Docket No.  
PO9-99-151

# Declaration and Power of Attorney For Patent Application

## English Language Declaration

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

### IDENTITY VECTORING VIA CHAINED MAPPING RECORDS

the specification of which

(check one)

☒ is attached hereto.

☐ was filed on \_\_\_\_\_ as United States Application No. or PCT International Application Number \_\_\_\_\_ and was amended on \_\_\_\_\_ (if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119(a)-(d) or Section 365(b) of any foreign application(s) for patent or inventor's certificate, or Section 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate or PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)			Priority Not Claimed
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/>
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/>
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/>

I hereby claim the benefit under 35 U.S.C. Section 119(e) of any United States provisional application(s) listed below:

_____	_____
(Application Serial No.)	(Filing Date)
_____	_____
(Application Serial No.)	(Filing Date)
_____	_____
(Application Serial No.)	(Filing Date)

I hereby claim the benefit under 35 U. S. C. Section 120 of any United States application(s), or Section 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. Section 112, I acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, C. F. R., Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application:

_____	_____	_____
(Application Serial No.)	(Filing Date)	(Status) (patented, pending, abandoned)
_____	_____	_____
(Application Serial No.)	(Filing Date)	(Status) (patented, pending, abandoned)
_____	_____	_____
(Application Serial No.)	(Filing Date)	(Status) (patented, pending, abandoned)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. *(list name and registration number)*

William B. Porter, Reg. No. 33,135  
 Floyd A. Gonzalez, Reg. No. 26,732  
 Lynn L. Augspurger, Reg. No. 24,227  
 William A. Kinnaman, Jr., Reg. No. 27,650  
 Lily Neff, Reg. No. 38,254  
 Marc A. Ehrlich, Reg. No. 39,966  
 Lawrence D. Cutter, Reg. No. 28,501

Christopher A. Hughes, Reg. No. 26,914  
 Edward A. Pennington, Reg. No. 32,588  
 John E. Hoel, Reg. No. 26,279  
 Joseph C. Redmond, Reg. No. 18,753  
 Philmore H. Colburn II, Reg. No. 35,101  
 Timothy J. Olson, Reg. No. 42,962

Send Correspondence to: **Philmore H. Colburn II**  
**Cantor Colburn LLP**  
**55 Griffin Road South**  
**Bloomfield, CT 06002**

Direct Telephone Calls to: *(name and telephone number)*  
**Philmore H. Colburn II (860) 688-4470**

Full name of sole or first inventor <b>Richard H. Guski</b>	
Sole or first inventor's signature	Date
Residence <b>197 Yantz Road, Red Hook, NY 12571</b>	
Citizenship <b>United States of America</b>	
Post Office Address <b>Same As Residence</b>	

Full name of second inventor, if any <b>Walter B. Farrell</b>	
Second inventor's signature	Date
Residence <b>35 Arnold Drive, Woodstock, NY 12498</b>	
Citizenship <b>United States of America</b>	
Post Office Address <b>Same As Residence</b>	

Full name of third inventor, if any <b>James W. Sweeny</b>	
Third inventor's signature	Date
Residence <b>RR3, Box 325, Horseshoe Road, Millbrook, NY 12545</b>	
Citizenship <b>United States of America</b>	
Post Office Address <b>Same As Residence</b>	

Full name of fourth inventor, if any <b>Thomas J. Szczygielski</b>	
Fourth inventor's signature	Date
Residence <b>113 Pine Knoll Road, Endicott, NY 13760</b>	
Citizenship <b>United States of America</b>	
Post Office Address <b>Same As Residence</b>	

Full name of fifth inventor, if any <b>John M. Thompson</b>	
Fifth inventor's signature	Date
Residence <b>27 Orchard Lane, West Sand Lake, NY 12196</b>	
Citizenship <b>United States of America</b>	
Post Office Address <b>Same As Residence</b>	

Full name of sixth inventor, if any	
Sixth inventor's signature	Date
Residence	
Citizenship	
Post Office Address	